

LAMIBLOC® laminated shims

For all special requirements

LAMIBLOC® laminated shims are used wherever conventional sizes are just not enough. Each 1 mm shim is composed of 20 layers, each 0.05 mm thick. The user can simply peel down the shim to the required thickness for machine alignment.



LAMIBLOC® laminated shims

- ▶ are exactly 1 mm thick and peel down easily in layers of 0.1 mm to the required thickness
- ▶ are available in 9 sizes and thus fit nearly all machine feet
- ▶ are made of stainless steel, thus offering long-term resistance against corrosion, acids and lyes
- ▶ are perfectly flat-rolled to avoid vibration and 'soft foot' when stacked together – even several millimetres at a time
- ▶ are a time- and money-saving, safe and practical alternative to hand-cut shims
- ▶ straightforward to work, allowing quick correction of soft foot and slanting foundations
- ▶ have rounded corners to prevent injury
- ▶ shims ALI 2.521 to ALI 2.526 are packed in reclosable cartons



LAMIBLOC® shims, dimensions and part numbers

Part No.	Dimensions				Packet size
	a	b	c	d	
ALI 2.521	43	43	12	22	10
ALI 2.522	53	53	14	27	10
ALI 2.523	68	68	16	34	10
ALI 2.524	98	98	25	49	10
ALI 2.525	118	118	30	59	10
ALI 2.526	200	200	36	100	10
ALI 2.527	300	200	36	240	10
ALI 2.528	400	200	42	330	10
ALI 2.529	1000	500	Sheet stock for custom shims	Sheet stock for custom shims	1

