

# LP364 Series



VIBRATION ANALYSIS HARDWARE

Dual Output Loop Power Sensor, 4-20 mA Output Proportional to Vibration in Acceleration with °C Temperature Output, Side Exit 3 Pin Connector



## Product Features

4-20 mA Current Proportional to Vibration in Acceleration

- ▶ Peak and RMS Outputs Available
- ▶ Transmits Signals Over Long Distances with No Signal Loss
- ▶ Outputs to PLC, DCS, SCADA

### LP364-XXX-1E

3 Pin Connector

Connector Pin	Polarity
A	(+) Loop Power mA Output
B	(-) Common
C	(+) Temperature Voltage

**Built To Order**

### LP364-XXX-2E

CB105 Molded Integral Cable

Conductor	Polarity
Red	(+) Loop Power mA Output
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire

**Built To Order**

### LP364-XXX-3E

CB218 Armored Integral Cable

Conductor	Polarity
Red	(+) Loop Power mA Output
Black	(-) Common
White	(+) Temperature Voltage
Shield	Cable Drain Wire

**Built To Order**

Specifications	Standard	Metric	Specifications	Standard	Metric
Part Number	LP364	M/LP364	<b>Physical</b>		
Temperature Output	10 mV/°C within the range -40°C to 85°C		Sensing Element	PZT Ceramic	
Tolerance: 4 mA	(± 10%)		Sensing Structure	Shear Mode	
Tolerance: 20 mA	(± 10%)		Weight	4.9 oz	140 grams
Tolerance: Temperature	(± 5°C)		Case Material	316L Stainless Steel	
<b>Electrical</b>			Mounting Thread	1/4-28	
Settling Time	<30 Seconds		Connector (Non-Integral)	3 Pin MIL-C-5015	
Voltage Source (IEPE)	15-30 VDC		Mounting Torque	2 to 5 ft. lbs.	2.7 to 6.8 Nm
Case Isolation	>10 <sup>8</sup> ohm		Mounting Hardware Supplied	1/4-28 Captive Bolt	M6x1 Captive Bolt
<b>Environmental</b>			Calibration Certificate	Current Output @ 100 Hz	
Operating Temperature Range	-4 to 212°F	-20 to 100°C			
Electromagnetic Sensitivity	CE				
Sealing	Welded, Hermetic				
Submersible Depth	200 ft.	60 m			

## Ordering Information

Stud Type	Measurement Range	Type	Frequency Range ±3dB	Style	Armor Length (Integral)	Cable Length (Integral)
Blank = 1/4-28 M = M6x1	00 = 0-1 g 02 = 0-2 g 05 = 0-5 g 10 = 0-10 g 20 = 0-20 g	P = Peak R = RMS	1 = 600-60000 CPM (10-1000 Hz) 2 = 180-150000 CPM (3-2500 Hz) 3 = 180-60000 CPM (3-1000 Hz) 4 = 180-300000 CPM (3-5000 Hz)	1E = 2 Pin MIL C-5015 2E = Integral Cable 3E = Armor Jacket	010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m	010 = 10 ft/3 m 020 = 20 ft/6 m 030 = 30 ft/9 m 050 = 50 ft/15 m 100 = 100 ft/30 m

Backed by our Unconditional Lifetime Warranty

www.ctconline.com | sales@ctconline.com | 585-924-5900

Custom Lengths Available Upon Request